




## LZF6127

Husqvarna's LZF series zero turn features a commercial-duty flat steel deck with reinforced 7 gauge side skirts, rolled front edge, welded front strip, and ribbed spindle with 7 gauge reinforcement plate for increased durability.



### UNIBODY FRAME

State-of-the-art, heavy-duty, welded steel uni-body frame provides increased strength and longer life.




### ROLL OVER PROTECTION SYSTEM (ROPS)

The practical foldable ROPS protects the user and can be lowered in areas with low-hanging branches.



### LARGE FUEL CAPACITY

11.4 gallons (Dual 5.7 gallon tanks) for up to 12 hours of mowing time. Large 3.5 inch diameter refill tube for easy refuelling.



### OPTIONAL LIGHT KIT

Optional high powered clamp on style headlights feature simplified installation, plug directly into harnesses on 2005+ units and are functional with existing key switch.

## Features

- Hydro system

- Ergonomic Steering Handles

TECHNICAL DATA	
Engine manufacturer	Kohler
Power	27 hp
Air Filter type	Heavy-Duty Canister Style
Fuel tank volume (with reserve)	11.4 gal.
Transmission type	Pump/Wheel motor
Wheel motors, cubic inch	Parker TJ with 1.25" shaft
Hydraulic reservoir	3 qt
Speed forward, min-max	0-10 mph
Speed reverse, min-max	0-5 mph
Cutting width	61 inch
Cutting deck type	Fabricated flat
Cutting height, min-max (approximate)	1.5 - 6 inch
Blades	4
Blade-tip speed	18600 fpm
Anti-scalp wheels	6
Deck lifting system	Quick Lift with foot assist
ROPS	Yes
Seat type	Standard
Hour meter	Digital
Cup holder	Yes
Tire size, front	13x6.5-6"
Tire size, rear	23x9.5-12"
Base machine, length	82 inch
Base machine, width (chute down)	66 inch
Base machine, width (chute up)	53 inch
Base machine, height	55 inch
Weight	1030 lbs
Productivity	4.3 acres/hr

ARTICLES	
966 95 68-01	LZF6127

